



Wire ————— Tinned copper
 Gauge ————— AWG 28/7 0,089 mm²
 Voltage rating ————— 300 Vr.m.s
 Current rating ————— 1,3 A at 10°C rise above ambient
 Capacity unbalanced ————— 78,7 pF/m nominal at 1MHz
 Impedance unbalanced ————— 75 Ω nominal
 Conductor resistance ————— 225 mΩ/m
 Propagation delay ————— 5,25 ns/m nominal
 Insulation material ————— PVC
 Temperature rating ————— -20°C (operating) | to +105°C
 ————— -30°C (static)
 Insulation resistance ————— 10 000 MΩ/km
 Approvals ————— UL Listed PLCC2-CL2
 ————— CSA Certified AWM FT-1

- ① : Flat cable, AWG 28/7
- ② : Clear polyester
- ③ : Paper liner
- ④ : Outer jacket: black PVC

09 18 050 7011	100 m (328 feet)
09 18 050 7008	30,48 m (100 feet)
Part number	Length per reel

			Dot.	Name	 All Dim. in mm Orig. Size DIN A 4
		Detail.	25/10/05	JMDR	
		Insp.			
		Stand.			
34612	20/09/07	PK	HARTING EURL F-95972 Paris		
33247	25/10/05	JMDR			
Mod.	Dot.	Name			

SEK 18 round flat cable, not shielded, 50 poles	Maßstab/ Scale
TB 09 18 050 70XX	Blatt/ Page 2 / 2
Sub.	