


Wire _____ Tinned copper
 Gauge _____ AWG 28/7 0,089 mm²
 Voltage rating _____ 300 Vr.m.s
 Current rating _____ 1,3 A at 10°C rise above ambient
 Capacity unbalanced _____ 45,9 pF/m at 1 MHz
 Impedance unbalanced _____ 105 Ω
 Propagation delay _____ 4,9 ns/m nominal
 Insulation material _____ PVC
 Temperature rating _____ -20°C (operating) to +105°C
 _____ -30°C (static)
 Flammability rating _____ Flame retardant VW1
 Insulation resistance _____ 10 000 MΩ/km
 Approval _____ UL AWM style 2651

A				Dot.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 flat cable 60 poles	Moßstab/ Scale	
				Detail.	20/10/05			JMDR	10:1
				Insp.					
				Stand.					
09 18 060 7004 100 m (328 feet) 09 18 060 7001 30,48 m (100 feet)		34400 18/09/07 PK 33246 20/10/05 JMDR		HARTING EURL F-95972 Paris		TB 09 18 060 700X		Blatt/ Page 1 / 1	
Part number		Length per reel		Mod.	Dot.	Name	Sub.		