



D	
C	<p>Wire _____ Tinned copper</p> <p>Gauge _____ AWG 28/7 0,089 mm<sup>2</sup></p> <p>Voltage rating _____ 300 Vr.m.s</p> <p>Current rating _____ 1,3 A at 10°C rise above ambient</p> <p>Capacity unbalanced _____ 45,9 pF/m at 1 MHz</p> <p>Impedance unbalanced _____ 105 Ω</p> <p>Propagation delay _____ 4,9 ns/m nominal</p> <p>Insulation material _____ PVC</p> <p>Temperature rating _____ -20°C (operating)          _____ -30°C (static) to +105°C</p> <p>Flammability rating _____ Flame retardant VW1</p> <p>Insulation resistance _____ 10 000 MΩ/km</p> <p>Approval _____ UL AWM style 2651</p>
B	
A	

09 18 037 7004	100 m (328 feet)
09 18 037 7001	30,48 m (100 feet)
Part number	Length per reel

				Dot.	Name	 All Dim. in mm Orig. Size DIN A 4	SEK 18 flat cable 37 poles	Moßstab/ Scale		
			Detail.	20/10/05	JMDR				10:1	
			Insp.						TB 09 18 037 700X	Blatt/ Page
			Stand.							1/1
			Mod.	Dot.	Name	HARTING EURL F-95972 Paris		Sub.		