

Han DD Quad module male



Part number	09 14 042 3001
Specification	Han DD Quad module male
HARTING eCatalogue	https://b2b.harting.com/09140423001

Identification

Category	Modules
Series	Han-Modular®
Type of module	Han DD® Quad module

Version

Termination method	Crimp termination
Gender	Male
Number of contacts	42
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.14 ... 2.5 mm²
Conductor cross-section	AWG 26 ... AWG 14
Rated current	10 A
Rated voltage	150 V
Rated impulse voltage	2.5 kV
Pollution degree	3
Rated voltage acc. to UL	250 V
Insulation resistance	> 10 ¹⁰ Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500

Material properties

Material (insert)	LCP
-------------------	-----



Pushing Performance

Material properties

Material flammability class acc. to UL 94 V-0

RoHS compliant

ELV status compliant

China RoHS e

REACH Annex XVII substances No

REACH ANNEX XIV substances No

REACH SVHC substances No

Specifications and approvals

UL / CSA UL 1977 ECBT2.E235076

Commercial data

Packaging size 1

Net weight 20.35 g

Country of origin Germany

European customs tariff number 85366990

eCI@ss 27440217 Module for industrial connectors (power/signals)