

M12 slim angled male D-cod 4-pol



| Part number | 21 03 881 3405 |
|--------------------|-------------------------------------|
| Specification | M12 slim angled male D-cod 4-pol |
| HARTING eCatalogue | https://b2b.harting.com/21038813405 |

Identification

| Category | Connector |
|----------------|-------------------------|
| Series | Circular connectors M12 |
| Identification | M12 Slim Design |
| Element | Cable connector |
| Specification | Angled |

Version

| Termination method | Crimp termination |
|--------------------|---|
| Gender | Male |
| Locking type | Screw locking |
| Shielding | Shielded |
| Number of contacts | 4 |
| Coding | D-coding |
| Details | Please order crimp contacts separately. |

Technical characteristics

| Conductor cross-section | 0.13 0.82 mm² |
|-------------------------|---|
| Conductor cross-section | AWG 26 AWG 18 |
| Wire outer diameter | ≤2.3 mm |
| Rated current | 4 A |
| Rated voltage | 250 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| Insulation resistance | ≥10 ⁸ Ω |
| Contact resistance | ≤10 mΩ |
| Ambient temperature | -40 +85 °C -5 +50 °C During connection |
| Tightening torque | 0.6 Nm |
| Wrench size | A/F 15 Knurled screw / knurled nut |



Technical characteristics

| Mating cycles | ≥500 |
|--|---------------------------------|
| Degree of protection acc. to IEC 60529 | IP65 when mated IP67 when mated |
| Cable diameter | 5.7 8.8 mm |
| Transmission characteristics | Cat. 5 Class D up to 100 MHz |
| Overvoltage category | III |
| Isolation group | I (600 ≤ CTI) |

Material properties

| Material (insert) | LCP |
|-----------------------------|---------------|
| Material (hood/housing) | Zinc die-cast |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | No |
| REACH ANNEX XIV substances | No |
| REACH SVHC substances | No |

Commercial data

| Packaging size | 10 |
|--------------------------------|----------|
| Net weight | 67.7 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |