

M12 transf. 10/100BASE-T d ANG w/ PoE+



Part number	21 03 381 4421
Specification	M12 transf. 10/100BASE-T d ANG w/ PoE+
HARTING eCatalogue	https://b2b.harting.com/21033814421

Identification

Category	Connector
Series	Circular connectors M12
Identification	M12 Magnetics
Element	PCB adapter
Specification	with integrated transformer Angled PoE enabled

Version

Termination method	Reflow soldering termination (SMT)
Gender	Female
Shielding	Shielded
Number of contacts	4
Coding	D-coding

Technical characteristics

Rated current	3 A
Rated voltage	57 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Insulation resistance	$> 10^8 \Omega$
Contact resistance	$\leq 10 \text{ m}\Omega$
Ambient temperature	-40 ... +85 °C +245 °C for reflow soldering
Mating cycles	≥ 100



Pushing Performance

Technical characteristics

Degree of protection acc. to IEC 60529	IP65 / IP67 when mated
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	100 Mbit/s

Material properties

Material (insert)	LCP
Material (contacts)	Brass
Surface (contacts)	Gold plated
RoHS	compliant with exemption
RoHS exemptions	6c: Copper alloy containing up to 4 % lead by weight 7c-I: Electrical and electronic components containing lead in a glass or ceramic other than dielectric ceramic in capacitors, e.g. piezoelectronic devices, or in a glass or ceramic matrix compound
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

Specifications and approvals

Specifications	IEC 61076-2-101
----------------	-----------------

Commercial data

Packaging size	30
Net weight	14.87 g
Country of origin	China
European customs tariff number	8536901100
eCl@ss	27440402 PCB connector