

M12 Power Crimp male L-coded



Part number	21 03 896 1505
Specification	M12 Power Crimp male L-coded
HARTING eCatalogue	https://b2b.harting.com/21038961505

Identification

Category	Connector
Series	Circular connectors M12
Identification	M12 Power
Element	Cable connector
Specification	Straight

Version

Termination method	Crimp termination
Gender	Male
Locking type	Screw locking
Shielding	Shielded
Number of contacts	4
FE contact	Yes
Coding	L-coding
Details	Please order crimp contacts separately.

Technical characteristics

Conductor cross-section	0.5 ... 2.5 mm ²
Conductor cross-section	AWG 20 ... AWG 14
Rated current	16 A
Rated voltage	63 V
Rated impulse voltage	1.5 kV
Pollution degree	3
Insulation resistance	>10 ⁸ Ω



Pushing Performance

Technical characteristics

Contact resistance	≤10 mΩ
Ambient temperature	-40 ... +85 °C
Tightening torque	0.6 Nm
Wrench size	A/F 17 Knurled screw / knurled nut
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 / IP67 when mated
Cable diameter	5.8 ... 13.5 mm
Overvoltage category	III
Isolation group	I (600 ≤ CTI)

Material properties

Material (insert)	PA
Material (hood/housing)	Zinc die-cast
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	No

Specifications and approvals

Specifications	IEC 61076-2-111
----------------	-----------------

Commercial data

Packaging size	1
Net weight	70 g
Country of origin	Romania
European customs tariff number	85366990
eCl@ss	27440102 Circular connector (for field assembly)