

M23 P HBM Back M25x1,5



Part number	09 15 600 0308
Specification	M23 P HBM Back M25x1,5
HARTING eCatalogue	https://b2b.harting.com/09156000308

Identification

Category	Hoods/Housings
Series	Circular connectors M23
Identification	Power
Type of hood/housing	Bulkhead mounted housing
Description of hood/housing	Straight Rear mounting
Version	
Locking type	Screw locking ComLock rapid locking
Size	M23
Fixing	Thread M25 x 1.5
Technical characteristics	
Limiting temperature	-40 +125 °C
Degree of protection acc. to IEC 60529	IP67 / IP69 / IPX9K acc. to ISO 20653 in locked position

Material properties

Material (hood/housing)	Copper-zinc alloy
Surface (hood/housing)	Nickel plated
Material (seal)	NBR
Colour (seal)	Black
RoHS	compliant
ELV status	compliant
China RoHS	e

Page 1 / 2 | Creation date 2019-10-11 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric GmbH & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Product data sheet 09 15 600 0308 M23 P HBM Back M25x1,5



Material properties

REACH Annex XVII substances	No		
REACH ANNEX XIV substances	No		
REACH SVHC substances	No		

Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076
Commercial data	
Packaging size	1
Net weight	46.3 g
Country of origin	Germany
European customs tariff number	85366990
eCl@ss	27440224 Shell for circular connectors