



TREDUX MA47, Medium wall adhesive lined

Features and Benefits

TREDUX MA47 medium wall heatshrink tubing with a shrink ratio of 4:1 is resistant to solvents, acids and alkaline solutions and offers especially good mechanical strength. The thermoplastic adhesive liner provides good moisture sealing and weathering protection.

TREDUX tubing are cut to lengths of 1 meter. Securely packed in display boxes, they can be removed individually for occasional use in smaller quantities.

Application

Suitable for insulation and protection of low voltage cable joints and terminations.



Medium wall tubing MA47 with shrink ratio 4:1 and adhesive liner.

Material Data

Material	Polyolefin, cross-linked (POX)
Colour	Black (BK)
Shrink Ratio	up to 4:1
Minimum Shrink Temperature	+120 °C
Operating Temperature	-55 °C to +80 °C
Dielectric Strength	20 kV/mm
Longitudinal change after shrinkage	-10% max



Technical Table

Article-No.	Type	Supplied Ø D	Recov. Ø d	Wall (WT) nom.	Pack Cont. (piece/1m)
323-50120	TREDUX MA47 - 12/3	12.0	3.0	2.00	6
323-50190	TREDUX MA47 - 19/6	19.0	6.0	2.50	10
323-50300	TREDUX MA47 - 30/8	30.0	8.0	2.50	6
323-50400	TREDUX MA47 - 40/12	40.0	12.0	2.50	4
323-50500	TREDUX MA47 - 50/16	50.0	16.0	2.70	2
323-50630	TREDUX MA47 - 63/19	63.0	19.0	2.80	2
323-50750	TREDUX MA47 - 75/22	75.0	22.0	3.00	2
323-50950	TREDUX MA47 - 95/30	95.0	30.0	3.00	1

All dimensions in mm. Subject to technical changes.