



### TREDUX HA47, Thick wall adhesive lined

#### Features and Benefits

TREDUX HA47 is a thick walled polyolefin adhesive lined tubing for low and medium voltage power applications. All tubings are cut to lengths of 1 meter. Securely packed in a display carton, they can be removed individually for occasional use in smaller quantities.

#### Application

The toughness and the weatherability of TREDUX thick wall tubing makes it suitable for exposed applications and underground cable joints.



TREDUX HA47 – application below ground.

#### Material Data

Material	<b>Polyolefin, cross-linked (POX)</b>
Colour	<b>Black (BK)</b>
Shrink Ratio	<b>up to 3.5:1</b>
Minimum Shrink Temperature	<b>+120 °C</b>
Operating Temperature	<b>-55 °C to +80 °C</b>
Dielectric Strength	<b>20 kV/mm</b>
Longitudinal change after shrinkage	<b>-10% max</b>



#### Technical Table

Article-No.	Type	Supplied Ø D	Recov. Ø d	Wall (WT) nom.	Pack Cont. (piece/1m)
321-50130	<b>TREDUX HA47 - 13/4</b>	13.0	4.0	2.40	6
321-50190	<b>TREDUX HA47 - 19/6</b>	19.0	6.0	2.70	10
321-50330	<b>TREDUX HA47 - 33/8</b>	33.0	8.0	3.20	5
321-50450	<b>TREDUX HA47 - 45/12</b>	45.0	12.0	4.10	4
321-50510	<b>TREDUX HA47 - 51/16</b>	51.0	16.0	4.10	2
321-50680	<b>TREDUX HA47 - 68/22</b>	68.0	22.0	4.10	1
321-50850	<b>TREDUX HA47 - 85/25</b>	85.0	25.0	4.30	1

All dimensions in mm. Subject to technical changes.