

HelaGuard HG-45FL 45° Elbow Swivel Flange, IP66

45° elbow swivel flange.

Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HG-45FL 45° Elbow Swivel Flange, IP66.

Technical Table

Article-No.	Type	Conduit Ø	Pack Cont.
166-23600	HG16-45FL	16	10
166-23601	HG21-45FL	21	10
166-23602	HG28-45FL	28	10
166-23603	HG34-45FL	34	10
166-23604	HG42-45FL	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.

Material Data

Material	Polyamide 6.6 (PA66)
Colour	Black (BK)
Operating Temperature	-50 °C to +135 °C
Flammability	UL94 V2



HelaGuard HGL-45FL 45° Elbow Swivel Flange, IP68

45° elbow swivel flange with conduit seal and washer.

Fulfils IP66, IP67, IP68 and IP69k.

Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HGL-45FL 45° Elbow Swivel Flange, IP68.

Technical Table

Article-No.	Type	Conduit Ø	Pack Cont.
166-24200	HGL16-45FL	16	10
166-24201	HGL21-45FL	21	10
166-24202	HGL28-45FL	28	10
166-24203	HGL34-45FL	34	10
166-24204	HGL42-45FL	42	2

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



Please note: for product specific approvals, please contact HellermannTyton.