

Helaguard PCS-FMC Compression Fitting, IP65

External thread, nickel plated brass.
Fulfils IP65.

Features and Benefits

- Multipart compression fitting including elastomeric seal
- Can be used for knockouts or threaded entries as fitting rotates until tightened



Helaguard PCS-FMC Compression Fitting.

Technical Table

Article-No.	Type	Conduit Ø	Thread Size (metric)	Thread Size (PG)	Pack Cont.
166-31400	PCS10-FMC-M12	10	M12	–	10
166-31401	PCS12-FMC-M16	12	M16	–	10
166-31402	PCS16-FMC-M16	16	M16	–	10
166-31409	PCS16-FMC-PG11	16	–	PG11	10
166-31403	PCS16-FMC-M20	16	M20	–	10
166-31404	PCS20-FMC-M20	20	M20	–	10
166-31410	PCS20-FMC-PG16	20	–	PG16	10
166-31405	PCS25-FMC-M25	25	M25	–	10
166-31411	PCS25-FMC-PG21	25	–	PG21	10
166-31406	PCS32-FMC-M32	32	M32	–	2
166-31412	PCS32-FMC-PG29	32	–	PG29	10
166-31407	PCS40-FMC-M40	40	M40	–	2
166-31408	PCS50-FMC-M50	50	M50	–	1

All dimensions in mm. Subject to technical changes.

Material Data

Material	Nickel Plated Brass (NPB), Polyamide 6 (PA6)
Colour	Metal (ML)
Operating Temperature	-40 °C to +135 °C

