



HARTING RJ Industrial®

Patch cable, overmoulded, 8-wire, Cat. 6

RJ45 connection cable for control or distributor cabinets or within controllers

RJ45 cords

PUR	<input checked="" type="checkbox"/>	8 wire	<input checked="" type="checkbox"/>	4 wire	<input type="checkbox"/>	Cat. 5e	<input type="checkbox"/>	Cat. 6	<input checked="" type="checkbox"/>	Cat. 6A	<input type="checkbox"/>	Cat. 7	<input type="checkbox"/>
-----	-------------------------------------	--------	-------------------------------------	--------	--------------------------	---------	--------------------------	--------	-------------------------------------	---------	--------------------------	--------	--------------------------

Connector types RJ45, overmoulded, with locking lever protection

Cable types 4 x 2, Twisted Pair, shielded, S/FTP
Category 7 acc. to IEC 61 156-6, EN 50 288-4-2

Sheath material PUR, halogen free LSZH

Wiring 8-pole, 1:1 or crossed

Transmission performance Category 6 / Class E up to 250 MHz
acc. to ISO/IEC 11 801:2002, EN 50 173-1

Transmission rate 10/100/1000 Mbit/s

Shielding Fully shielded, 360° shielding contact

Operating temperature range 0 °C ... +60 °C

Standard lengths 0.5 m / 1 m / 2 m / 3 m / 5 m / 10 m
other lengths available on request

Colour Yellow

Advantages

- Robust industrial design
- Easy handling for all applications
- Halogen free
- RoHS compliant