


## Q-ties, Polyamide 6.6 UV-resistant (PA66W), black

Application Tool	Registration Numbers
MK3SP	1
MK3PNSP2, MK7P	2
MK7	3
MK7HT	4
MK20	5
MK6	6
MK9P	7
MK9	8
MK9HT	9
MK21	10

For detailed information on Application Tools please refer to page 15.



Q-tie cable ties: choose from a wide product range in different materials.



Q-tie cable tie

Material Data	
Material	<b>Polyamide 6.6 UV-resistant (PA66W)</b>
Colour	<b>Black (BK)</b>
Operating Temperature	<b>-40 °C to +85 °C continuous, (+105 °C for 500 h)</b>
Flammability	<b>UL94 V2</b>



Technical Table

Article-No.	Type	Length (L)	Width (W)	Bundle Ø max.	Min. Tensile Strength (N)	Material	Colour	Application Tool
Polyamide 6.6. UV Stabilised								
109-00059	Q18R	105	2.6	24.0	80	PA66W	Black (BK)	1-3, 5
109-00062	Q18I	155	2.6	40.0	80	PA66W	Black (BK)	1-3, 5
109-00065	Q18L	195	2.6	50.0	80	PA66W	Black (BK)	1-3, 5
109-00068	Q30R	160	3.6	38.0	130	PA66W	Black (BK)	1-3, 5
109-00070	Q30L	200	3.6	50.0	130	PA66W	Black (BK)	1-3, 5
109-00072	Q30LR	250	3.6	65.0	130	PA66W	Black (BK)	1-3, 5
109-00076	Q50R	210	4.7	50.0	220	PA66W	Black (BK)	1-10
109-00078	Q50I	290	4.7	75.0	220	PA66W	Black (BK)	1-10
109-00080	Q50L	410	4.7	110	220	PA66W	Black (BK)	1-10
109-00082	Q120I	300	7.7	70.0	530	PA66W	Black (BK)	6-10
109-00084	Q120R	420	7.7	110	530	PA66W	Black (BK)	6-10
109-00086	Q120M	520	7.7	145	530	PA66W	Black (BK)	6-10

All dimensions in mm. Subject to technical changes.