


Q-tags, Identification Tags

Features and Benefits


Q-tags are used to identify a cable or a cable bundle and are secured with a Q-tie. The Q-tag's flag design allows the user to quickly read or scan the printed information. The tags can be marked by hand with a marker pen (T82 series) or with a printed adhesive label. HellermannTyton offers a complete printing solution for Q-tags: printers, labels, ribbons, and market leading label design software; Tagprint Pro V2. Using Q-ties and Q-tags gives users the confidence that cables and cable bundles are safely secured and the text is highly visible.




The flagged orientation of Q-tags ensures that printed texts are easily visible.



Q-tag QT7016R



Q-tag QT7040R



Q-tag QT7040S



Q-tags are available in different sizes and types.



Q-tags can be labelled with pre-printed labels or by hand.

Material Data	
Material	Polyamide 6.6 (PA66)
Colour	White (WH)
Operating Temperature	-40 °C to +85 °C continuous, (+105 °C for 500 h)
Flammability	UL94 V2



Technical Table

Article-No.	Type	Length (L)	Length (L2)	Width (W)	Strap Width max. (G)	Pack Cont.	Colour
151-10950	QT7016R	100.0	70.0	18.0	4.7	50	White (WH)
151-10951	QT7040R	100.0	70.0	42.0	4.7	50	White (WH)
151-10952	QT7040S*	100.0	70.0	42.0	3.6	50	White (WH)
151-10953	QT10065R	135.0	100.0	67.0	4.7	25	White (WH)
Marker pens T82							
500-50820	T82S-BK	-	-	-	-	2	Black (BK)
500-50822	T82R-RD	-	-	-	-	2	Red (RD)

* right angled