




# High-Current Through and Ground Conductor Terminal Blocks

## 185 mm<sup>2</sup> 285 Series

50 - 185 mm <sup>2</sup>   2/0 AWG - 350 kcmil 1000 V AC/DC/1500 VDC/12 kV/3 ① I <sub>N</sub> 353 A  Terminal block width 32 mm / 1.26 in  45 - 47 mm / 1.77 - 1.85 in ②	50 - 120 mm <sup>2</sup>   1/0 AWG - 250 kcmil  Terminal block width 32 mm / 1.26 in  45 - 47 mm / 1.77 - 1.85 in ②
---	---



Item No.	Pack. Unit	Item No.	Pack. Unit
<b>2-conductor through terminal block,</b> to be used exclusively on DIN 35 x 15 rail ● gray <b>285-1185</b> 5 ● blue <b>285-1184</b> 5		<b>2-conductor ground terminal block,</b> to be used exclusively on DIN 35 x 15 rail; 2.3 mm thick, copper ● green-yellow <b>285-1187</b> 5	
<b>Item-Specific Accessories</b>		<b>Item-Specific Accessories</b>	
<b>Steel carrier rail,</b> acc. to EN 60715, 35 x 15 mm, 2.3 mm, 2 m/6'6" long unslotted <b>210-118</b> 10		<b>Copper carrier rail,</b> acc. to EN 60715, 35 x 15 mm, 2.3 mm, 2 m/6'6" long unslotted <b>210-198</b> 10	
<b>Copper carrier rail,</b> acc. to EN 60715, 35 x 15 mm, 2.3 mm, 2 m/6'6" long unslotted <b>210-198</b> 10			

### 285 Series Accessories

Appropriate marking systems: WMB/Marking strips/WMB Inline  
(see Full Line Catalog, Volume 1, Section 13)

<b>Adjacent jumper,</b> insulated, I <sub>N</sub> 309 A for 1 jumper gray <b>285-1171</b> 25	<b>WMB Inline,</b> plain, stretchable 5 - 5.2 mm, 1,500 WMB markers, 5 mm, on roll white <b>2009-115</b> 1
<b>Protective warning marker,</b> with high-voltage symbol, black yellow <b>285-1177</b> 50 (2x25)	<b>Marking strip,</b> plain, 11 mm wide, 50 m roll white <b>2009-110</b> 1
<b>Finger guard,</b> touchproof cover protects unused conductor entries and jumper slots yellow <b>285-1178</b> 25	<b>WMB Multi marking system,</b> 10 strips with 10 markers per card, for terminal widths 5 - 17.5 mm plain <b>793-501</b> 5
<b>Allen wrench with partially insulated shaft</b> <b>285-172</b> 1	<b>WMB Multi marking system,</b> 10 strips with 10 markers per card, stretchable 5 - 5.2 mm plain <b>793-5501</b> 5
<b>Three-phase set,</b> with 35mm <sup>2</sup> high-current terminal blocks <b>285-1169</b> 1	
<b>Screwless end stop,</b> for DIN 35 rail, 14 mm wide gray <b>249-197</b> 10	

- 1 AC/DC up to 1000 V = rated voltage  
DC up to 1500 V  
12 kV = rated surge voltage  
3 = pollution degree  
(see Full Line Catalog, Volume 1, Section 14)
- 2 Strip length, see packaging or instructions.

