



LRT, RT250 Series Releasable Ties

Features and Benefits

The extended pawl allows for quick and simple release of the ties. An eyelet on the head of the ties allows any excess tail to be tucked neatly away - this also helps to prevent the trigger from accidental release


Application

Used in a wide range of industries these releasable and reusable ties are ideal where temporary installation or the addition or removal of cables is required, for example: theatres, outdoor events or harness work.


These ties are ideal for larger or heavier applications.



Ideal for larger or heavier bundles these ties can be opened and reused.



Material Data	
Material	Polyamide 6.6 UV Resistant (PA66W)
Operating Temperature	-40 °C to +85 °C Continuous, (+105 °C for 500 h)
Flammability	UL94 V2



LRT, RT250 Series

Technical Table

Article-No.	Type	Length (L)	Width (W)	Bundle Ø max.	Min. Tensile Strength (N)	Material	Colour	Application Tool
111-70400	LRT230	230	7.6	52.0	535	PA66	Black (BK)	6-9
131-75819	RT250S	230	12.5	50.0	1115	PA66	Natural (NA)	9
115-41800	RT250S	230	12.5	50.0	1115	PA66	Black (BK)	9
115-41803	RT250S	230	12.5	50.0	1115	PA66W	Black (BK)	9
131-75019	RT250R	515	12.5	127	1115	PA66	Natural (NA)	9
115-41300	RT250R	515	12.5	127	1115	PA66	Black (BK)	9
115-41303	RT250R	515	12.5	127	1115	PA66W	Black (BK)	9
131-75619	RT250M	565	12.5	150	1115	PA66	Natural (NA)	9
131-75610	RT250M	565	12.5	150	1115	PA66	Black (BK)	9
131-75620	RT250M	565	12.5	150	1115	PA66W	Black (BK)	9
131-75219	RT250I	735	12.5	203	1115	PA66	Natural (NA)	9
115-41401	RT250I	735	12.5	203	1115	PA66	Black (BK)	9
115-41403	RT250I	735	12.5	203	1115	PA66W	Black (BK)	9
131-75419	RT250L	889	12.5	254	1115	PA66	Natural (NA)	9
131-75519	RT250XL	1030	12.5	305	1115	PA66	Natural (NA)	9
131-75510	RT250XL	1030	12.5	305	1115	PA66	Black (BK)	9
131-75560	RT250XL	1030	12.5	305	1115	PA66W	Black (BK)	9

All dimensions in mm. Subject to technical changes.



Please Note for Product Specific Approvals please refer to the Appendix