

### HelaGuard HG-DC Double Slit

Double slit corrugated conduit for retrofitting.

#### Features and Benefits

- Can be opened and closed repeatedly
- Cables can be inserted laterally
- Abrasion resistant
- Free of halogen, sulphur and phosphorus
- Colour: black (UV resistant)

#### Application

Control panels, machine building, plant construction and wherever retrofitting is a requirement.



HelaGuard HG-DC double slit conduit is ideal for retrofitting.

**Other materials  
available on request.  
Please contact us!**

#### Material Data

Material	<b>Polyamide 6 (PA6)</b>
Operating Temperature	<b>-40 °C to +110 °C</b>
Flammability	<b>UL94 V2</b>



#### Technical Table

Article-No.	Type	Nominal Ø	Outside Ø (OD)	Ø D	Bending Radius	Weight (g/m)	Reel Length (m)	Colour
166-11800	<b>HG-DC11</b>	11	11.5	6.7	45	23	50	Black (BK)
166-11801	<b>HG-DC13</b>	13	13.0	7.9	55	37	50	Black (BK)
166-11802	<b>HG-DC16</b>	16	15.8	10.5	60	44	50	Black (BK)
166-11803	<b>HG-DC21</b>	21	21.2	13.9	90	63	50	Black (BK)
166-11804	<b>HG-DC28</b>	28	28.5	20.5	105	94	50	Black (BK)
166-11805	<b>HG-DC34</b>	34	34.5	27.0	150	118	25	Black (BK)
166-11806	<b>HG-DC42</b>	42	42.5	34.8	170	193	25	Black (BK)
166-11807	<b>HG-DC54</b>	54	54.5	45.3	170	263	25	Black (BK)

All dimensions in mm. Subject to technical changes.

Other reel lengths available on request.



Please note: for product specific approvals, please contact HellermannTyton.