

## HelaGuard HG-SM Straight Swivel External Thread, IP66

Straight swivel brass external thread.

### Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HG-SM Straight Swivel External Thread, IP66.

Technical Table

Article-No.	Type	Conduit Ø	Thread Size (metric)	Thread Size (PG)	Pack Cont.
166-21300	HG13-SM-M16	13	M16	–	10
166-21309	HG13-SM-PG9	13	–	PG9	10
166-21301	HG16-SM-M16	16	M16	–	10
166-21302	HG16-SM-M20	16	M20	–	10
166-21310	HG16-SM-PG9	16	–	PG9	10
166-21311	HG16-SM-PG11	16	–	PG11	10
166-21303	HG21-SM-M20	21	M20	–	10
166-21312	HG21-SM-PG13	21	–	PG13.5	10
166-21313	HG21-SM-PG16	21	–	PG16	10
166-21304	HG28-SM-M25	28	M25	–	10
166-21314	HG28-SM-PG21	28	–	PG21	10
166-21305	HG34-SM-M32	34	M32	–	10
166-21315	HG34-SM-PG29	34	–	PG29	10
166-21306	HG42-SM-M40	42	M40	–	2
166-21307	HG54-SM-M50	54	M50	–	2
166-21308	HG67-SM-M63	67	M63	–	1

All dimensions in mm. Subject to technical changes.

Colour grey available on request.

Material Data

Material	<b>Polyamide 6.6 (PA66), Nickel Plated Brass (NPB)</b>
Colour	<b>Black (BK)</b>
Operating Temperature	<b>-50 °C to +135 °C</b>
Flammability	<b>UL94 V2</b>



## HelaGuard HGL-SM Straight Swivel External Thread, IP68

Straight swivel brass external thread with conduit seal and washer.

Fulfils IP66, IP67, IP68 and IP69k.

### Features and Benefits

- One piece, fast fit
- High pull-off strength
- Highly resistant to solvents and oils
- Free of halogen, sulphur and phosphorus



HelaGuard HGL-SM Straight Swivel External Thread with conduit seal, IP68.

Technical Table

Article-No.	Type	Conduit Ø	Thread Size (metric)	Thread Size (PG)	Pack Cont.
166-21900	HGL13-SM-M16	13	M16	–	10
166-21909	HGL13-SM-PG9	13	–	PG9	10
166-21901	HGL16-SM-M16	16	M16	–	10
166-21902	HGL16-SM-M20	16	M20	–	10
166-21910	HGL16-SM-PG9	16	–	PG9	10
166-21911	HGL16-SM-PG11	16	–	PG11	10
166-21903	HGL21-SM-M20	21	M20	–	10
166-21912	HGL21-SM-PG13	21	–	PG13.5	10
166-21913	HGL21-SM-PG16	21	–	PG16	10
166-21904	HGL28-SM-M25	28	M25	–	10
166-21914	HGL28-SM-PG21	28	–	PG21	10
166-21905	HGL34-SM-M32	34	M32	–	10
166-21915	HGL34-SM-PG29	34	–	PG29	10
166-21906	HGL42-SM-M40	42	M40	–	2
166-21907	HGL54-SM-M50	54	M50	–	2
166-21908	HGL67-SM-M63	67	M63	–	1

All dimensions in mm. Subject to technical changes.

Colour grey available on request.



Please note: for product specific approvals, please contact HellermannTyton.